


# Fibocom FG132 M.2 Series

5G Redcap Wireless Module Designed Specifically for IoT Applications

## Key Benefits

- Dual-mode support for 5G RedCap and 4G LTE
- Low latency and low power consumption for 5G
- Rich functionality interfaces greatly expand application scenarios



- Take FG132-GL as an example
- Product rendering is for reference only.
- Certification information is subject to the specifications below



Release 17



5G Redcap



M.2 Package



GNSS



Fibocom Enhanced  
AT Commands



Professional Reference  
Design, Evaluation Kits

Fibocom FG132 M.2 Series is a high-performance 5G Redcap Sub-6 GHz wireless communication module. It supports 3GPP R17 RedCap technology, offering a maximum downlink speed of 223Mbps and uplink speed of 123Mbps under the 5G RedCap network, maximum downlink speed of 195Mbps and uplink speed of 75Mbps under the LTE network. It supports 5G SA networks, backward compatibility with 4G, and caters to 5G private networks and slicing requirements.

Fibocom FG132 M.2 Series share a standard M.2 PIN layout, offering two size for choice, containing Global version and Chinese version to meet different market demands.

Positioned for mid-rate IoT markets including industrial routers, Industrial PC, IP cameras, IoT gateways, fixed wireless access terminals, etc.



5G Redcap	FG132-GL-00-M2	FG132-GL-00-M2-10	FG132-CN M.2
Region	Global	Global	China
Basic Features			
Package	M.2		
Dimension (mm)	(52.0±0.15) mm x (30.0±0.15) mm x (3.2±0.2) mm	(42.0±0.15) mm x (30.0±0.15) mm x (3.2±0.2) mm	(52.0±0.15) mm x (30.0±0.15) mm x (3.2±0.2) mm
5G NR SA	N1/2/3/5/7/8/12/13/14/18/20/25/26/28/30/38/40/41/48/66/70/71/77/78	N1/2/3/5/7/8/12/13/14/18/20/25/26/28/30/38/40/41/48/66/70/71/77/78	N1/3/5/8/28/40/41/78/79
LTE Bands	B1/2/3/4/5/7/8/12/13/14/17/18/19/20/25/26/28/30/34/38/39/40/41/42/43/48/66/71	B1/2/3/4/5/7/8/12/13/14/17/18/19/20/25/26/28/30/34/38/39/40/41/42/43/48/66/71	B1/3/5/8/34/38/39/40/41
LTE-HPUE	B38/40/41/42/43	B38/40/41/42/43	B38/41
Power Supply	3.3V ~ 4.3V, Typical 3.8V		
Operating Temperature	-35° C ~ +75° C		
Extended Temperature	-40°C ~ +85°C		
ROM+RAM	2Gb+2Gb		
Antenna	Main+Div+GNSS		
Data Transmission			
5G SA Sub-6 (256QAM)	223Mbps (DL) /123Mbps (UL)		
LTE (256QAM)	195Mbps (DL) /75Mbps (UL)		
Functions			
Protocols	TCP/UDP/NTP/NITZ/HTTP/PING/HTTPS/SSL/FILE/MQTT/CoAP/LwM2M		
FOTA	DFOTA		
OS Drivers	Linux/Windows/Android		
VoNR/VoLTE	●		
GNSS	●		
OpenCPU	●		
ESIM	Optional		
Interfaces			
SIM	●		
USB	● USB 2.0		
PCIE	●		
PCM	●		
ANT_CTL	●		
LED	●		
Certification			
Regulation	FCC / CE / RCM / RoHS / REACH / HF / TSCA / GCF/ PTCRB/RCM/REACH	FCC / CE / RCM / RoHS / REACH / HF / TSCA / GCF/ PTCRB/RCM/REACH	CCC/SRRC/NAL/ROHS
Operator	T-Mobile*/Verizon*/AT&T*	T-Mobile*/Verizon*/AT&T*	NA

\* = Planning /Under development    ● = Support

Fibocom Wireless Inc.

Telephone: +86 755-26733555    Email: info@fibocom.com  
Address: Floor 10th, Tower A, Building 6, Shenzhen International  
Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China  
Official website: www.fibocom.com

