

Table Business Phone

VOIP Video Phone

SC39-G

- 4G call
- Remote Management



Overview

SC39-G smart telephone use CortexA55 1.8G*quad-core design, support HD voice, The original ecological Android 11.10 system design supports application expansion based on the open Android platform, The device uses a 8.0 inch 1280x800IPS high-definition resolution display, the capacitive screen with multi-touch. Supports RJ45 wired network, and meets various network connections. Input method.

SC39-G supports HD audio/video calls based on the SIP protocol, and has excellent hardware echo suppression and noise reduction effects; supports the standard SIP2.0 protocol, and is compatible with mainstream soft switches, IMS and IPPBX systems on the market, as well as various SIP protocol mainstream audio/video terminal.



HD voice



8-inch
IPS screen



Dual gigabit
network
interface



Audio and
video
conference



Earphone



Call
Recording



POE power
supply



6 SIP
account



4G call

Product Highlight

Good user experience

The appearance is simple and generous, equipped with 8 inch HD display, with color display, clear operation interface design, visual effect is better. At the same time, SC39-G back buckle bracket design, perfect fit with the desktop, easy to use, firm.

Powerful & good expansibility

Built-in 2.4G/5G WiFi module, 2 double gigabit network ports, make the network connection more flexible and convenient. One PSTN port, which can be connected to a telephone line at the same time, supports 4G plug-in phones to meet customer requirements in different scenarios. With USB interface, can be extended to store call recording. Support HDMI interface, POE power supply, Type-C interface and power cable power supply, a variety of charging methods to meet customer needs.

HD AUDIO

it has professional audio processing technology to make the sound quality clearer, 3W full frequency speaker and super large sound cavity, bringing users a high-quality hands-free calling experience, The 5 million high-definition camera can be blocked and the angle of the camera can be adjusted, and it supports up to 1080P video calls. By combining advanced algorithms with rich experience in the network, it can be used even under extremely challenging network conditions. Can provide excellent video quality.

Secure Deployment Configuration Protocol

Users do not need to manually configure and upgrade the phone, just need to power on and connect to the Internet, and the phone can be automatically deployed, saving a lot of time and cost.

Technical Parameters

AUDIO

- HD Voice Microphone/Speaker(Handset/Hands-free)
- Excellent Echo Cancellation Technology(ECT)
- Receiver with intelligent noise reduction ANC Technology
- Audio codec:
G.722,GSM,PCMA,PCMU,G.729AB,iLBC,AMR,DTMF,ISACW
B,ISACSWB,OPUS
- Video codec:H264,VP8,720P 30fps
- DTMF:In-band、Out-of-band(RFC2833)、SIPINFO
- Full duplex hands-free
- VAD, CNG, AEC, AGC, ANS

Phone Features

- 6 SIP accounts
- Call hold/mute/DND/redial/One-touch speed dial
- Call forward/call transfer/blind transfer
- Redial/Callback/Auto answer
- Call log: all/out/received/missed/call forward
- 6-way conferences
- Direct IP call without SIP proxy
- Ringer selection
- Set date time manually or automatically
- Built-in WIFI: Standard: IEEE802.11 b/g/n
Band: 2.4GHz/5.0GHz
- Basic function: received/hand up/call mute
- Customize app: DSS key

Directory

- Phone book (1000 records)
- Backlist
- Intelligent search/Phone book search/import/export
- Tree enterprise phone book/LDAP phone book

Phone interface

- Incoming call/missed message led indicator
- Intuitive user interface
- support Chinese/English or other languages
- Incoming call show name and number

Interface

- 2*RJ45 double Gigabit network port
- POE IEEE 802.3af
- 1*TF card interface
- 1*Type-C interface
- 1*PSTN interface
- 1*Power interface
- 1*RJ9(4P4C) handle interface
- 1*HDMI interface
- 1*SIM card interface

Management

- Online APP update,WEB terminal offline update
- Support PnP auto provisioning mode
- TR069 remote provisioning
- Reset to factory, reboot
- Packet capture and export system log

Network and Security

- Call server redundancy supported
- NAT Traversal By STUN
- Proxy mode and peer-to-peer SIP link mode
- IP address allocation mode: static/dynamic
- Support HTTP web server
- Time and date synchronization using SNTP
- Support UDP/TCP/TLS
- QoS: DSCP
- Support SRTP

Others

- BLF
- Intercom,multicast
- Message Prompt
- Voice message,switch account
- Call Park,Call pickup
- Call completion, Call recording
- Server-based recording function
- Voice message led indicator
- Power led indicator

PSTN Feature

- Support FSK/DTMF
- Answering: Automatic Answering/Workday Answering
- Calling Region Checking/auto dialing with “0”

4G Function

- TDD-LTE/FDD-LTE/Nano sim Card *1

Other physical

- Color: Black
- Power adapter: 12V/1A DC input
- Relative humidity: 10%~90% No Condensing
- Operation temperature: -10~50 °C

Package Contents

- Package list:
SC39-G phone/handset/bracket/camera/power adapter/
line cord/coil cord/user manua
N.W/CTN: 6.4kg
O.G.W/CTN: 7kg
- GIFT BOX SIZE:345*275*128mm
- MASTER CARTON SIZE:534*361*297mm

