



FG132-GL-00

RF Test Report

V1.1

Disclaimer

Any action you take in the course of using this document is at your own risk, and Fibocom shall not be liable for any damages or losses under any circumstances. Due to product version upgrade or other reasons, Fibocom reserves the right to modify any information in this document at any time without prior notice and any responsibility. Unless otherwise agreed, all statements, information and suggestions in this document do not constitute any express or implied guarantee.

This document may include the third-party information covering products, services, software, data, and so on. Fibocom does not control and assumes no responsibility for the third-party content, including but not limited to the accuracy, compatibility, reliability, availability, legitimacy, appropriateness, performance, non-infringement, and status update, unless otherwise specified in this document. Fibocom does not provide any guarantee or authorization for the third-party content mentioned or referenced in this document. If you need a third-party license, obtain it in an authorized or legal way, unless otherwise specified in this document.

Copyright Notice

Copyright © 2025 Fibocom Wireless Inc. All rights reserved.

Unless specially authorized by Fibocom, the recipient of the documents shall keep the documents and information received confidential, and shall not use them for any purpose other than the implementation and development of this project. Without the written permission of Fibocom, no unit or individual shall extract or copy part or all of the contents of this document without authorization, or transmit them in any form. Fibocom has the right to investigate legal liabilities for any offense and tort in connection with violation of confidentiality obligations, or unauthorized use or malicious use of the said documents and information in other illegal forms.

Trademark Statement

 The trademark is registered and owned by Fibocom Wireless Inc.

Other trademarks, product names, service names and company names appearing in this document are owned by their respective owners.

Contact Information

Website: <https://www.fibocom.com>

Address: 10/F-14/F, Block A, Building 6, Shenzhen International Innovation Valley, Dashi First Road, Xili Community, Xili Subdistrict, Nanshan District, Shenzhen

Tel: 0755-26733555

Contents

Change History.....	2
1 Test Version Description	3
2 Test Device	4
3 Test Summary	5
4 Test Standards and Conditions	6
4.1 Test Standards	6
4.2 Test Environment	6
5 Test Items.....	7
5.1 LTE FDD Specifications.....	7
5.2 LTE TDD Specifications.....	13
5.3 LTE HPUE Specifications.....	16
5.4 5G RedCap FDD Specifications	17
5.5 5G RedCap TDD Specifications.....	23
5.6 5G RedCap SRS Specifications	27
5.7 GNSS Specifications.....	27
5.8 Max Throughput.....	27
5.9 Working Current.....	32

Change History

V1.1(2025-03-06)	The chapter 5.6 add the SRS specifications
V1.0 (2024-10-09)	Initial version

1 Test Version Description

Table 1. Test version description

Product name	FG132-GL-00
Hardware version	V1.3
Software version	19003.1000.00.02.01.46

2 Test Device

Table 2. Test device list

No.	Device Name	Manufacturer	Model
1	Programmable constant temperature and humidity test chamber	XI'AN HUANKE Equipment Co., Ltd.	TEST GDJS-100C
2	Wideband radio communication tester	R&S	CMW500
3	Wideband radio communication tester	Anritsu	MT8821C
4	Wideband radio communication tester	R&S	CMX500
5	Wideband radio communication tester	Keysight	E7515R
6	DC power Analyzer	KEYSIGHT	N6705C
7	DC power supply	Agilent	66309D/66319D
8	Vector Signal Generator	R&S	SMBV100B

3 Test Summary

Table 3. Summary of test items

No.	Test Item	Test Result	Remarks (Failed Item)
1	LTE FDD	PASS	--
2	LTE TDD	PASS	--
3	LTE HPUE	PASS	--
4	5G RedCap FDD	PASS	--
5	5G RedCap TDD	PASS	--
6	5G RedCap SRS	PASS	--
7	GNSS	PASS	--
8	Max Throughput	PASS	--
9	Working Current	PASS	--

4 Test Standards and Conditions

4.1 Test Standards

Table 4. Supported systems and followed standards

No.	Communication System	Reference Standard/Specification
1	LTE	3GPP TS 36.521-1
2	5G RedCap	3GPP TS 38.521-1
3	GNSS	Product Specifications

4.2 Test Environment

Table 5. Test environment

No.	Test Environment	Test Temperature	Power Supply Voltage
1	Normal/NC	Normal temperature/room temperature: +25°C	Normal voltage: +3.8V
2	TL/VL	Low operating temperature: -35°C	Low voltage: +3.3V
3	TL/VH	Low operating temperature: -35°C	High voltage: +4.3V
4	TH/VL	High operating temperature: +75°C	Low voltage: +3.3V
5	TH/VH	High operating temperature: +75°C	High voltage: +4.3V

5 Test Items

5.1 LTE FDD Specifications

Description:

The maximum TX power of LTE FDD is measured by 10M QPSK 1RB. The RB position in low and medium channels is low, and the RB position in high channel is high.

Table 6. LTE-FDD maximum TX power & RX sensitivity (main+diversity) (Bandwidth=10M)

Band	Channel	Maximum TX Power (dBm)			RX Sensitivity (Main+Diversity) (dBm)		
		3GPP Requirement	Test Value		3GPP Requirement	Test Value	
			1460#	8110#		1460#	8110#
B1	L	23.0±2.7	23.2	23.1	-96.3	-102.1	-102.1
	M	23.0±2.7	23.2	23.2		-102.3	-102.1
	H	23.0±2.7	23.1	23.1		-102.1	-101.9
B2	L	23.0+2.7/-4.2	23.1	23.0	-94.3	-102.3	-101.9
	M	23.0±2.7	23.2	23.0		-102.5	-102.3
	H	23.0+2.7/-4.2	23.1	22.9		-102.5	-102.5
B3	L	23.0+2.7/-4.2	23.0	23.0	-93.3	-101.7	-101.9
	M	23.0±2.7	23.1	23.1		-102.3	-102.1
	H	23.0+2.7/-4.2	23.1	23.0		-102.3	-102.3
B4	L	23.0±2.7	22.9	22.9	-96.3	-102.1	-101.9
	M	23.0±2.7	23.0	23.0		-102.5	-102.3
	H	23.0±2.7	22.9	23.0		-101.9	-101.9
B5	L	23.0±2.7	23.4	23.3	-94.3	-102.9	-103.1
	M	23.0±2.7	23.4	23.3		-102.9	-102.7
	H	23.0±2.7	23.3	23.2		-102.7	-102.7
B7	L	23.0+2.7/-4.2	22.9	22.7	-94.3	-101.9	-101.9
	M	23.0±2.7	22.8	22.7		-101.7	-101.5
	H	23.0+2.7/-4.2	23.0	22.9		-101.5	-101.3
B8	L	23.0+2.7/-4.2	23.4	23.3	-93.3	-102.7	-102.5
	M	23.0±2.7	23.5	23.3		-102.7	-102.5
	H	23.0+2.7/-4.2	23.3	23.3		-102.5	-102.5

Band	Channel	Maximum TX Power (dBm)			RX Sensitivity (Main+Diversity) (dBm)		
		3GPP Requirement	Test Value		3GPP Requirement	Test Value	
			1460#	8110#		1460#	8110#
B12	L	23.0+2.7/-4.2	23.2	23.1	-93.3	-101.9	-101.7
	M	23.0±2.7	23.2	23.2		-101.9	-101.9
	H	23.0+2.7/-4.2	23.2	23.2		-102.1	-101.9
B13	L/M/H	23.0±2.7	23.2	23.1	-93.3	-102.1	-101.9
B14	L/M/H	23.0±2.7	23.2	23.1	-93.3	-101.7	-101.7
B17	L	23.0±2.7	23.2	23.1	-93.3	-102.1	-101.9
	M	23.0±2.7	23.2	23.2		-102.1	-101.9
	H	23.0±2.7	23.2	23.1		-102.1	-102.1
B18	L	23.0+2.7/-4.2	23.2	23.2	-96.3	-102.7	-102.7
	M	23.0±2.7	23.3	23.2		-102.7	-102.7
	H	23.0±2.7	23.4	23.3		-102.7	-102.5
B19	L	23.0±2.7	23.4	23.3	-96.3	-102.9	-102.9
	M	23.0±2.7	23.4	23.3		-102.7	-102.5
	H	23.0±2.7	23.4	23.3		-102.7	-102.5
B20	L	23.0+2.7/-4.2	23.3	23.3	-93.3	-102.5	-102.3
	M	23.0±2.7	23.4	23.3		-102.7	-102.3
	H	23.0+2.7/-4.2	23.4	23.3		-102.5	-102.5
B25	L	23.0+2.7/-4.2	23.2	23.0	-92.8	-102.2	-102.0
	M	23.0±2.7	23.2	23.0		-102.6	-102.2
	H	23.0+2.7/-4.2	23.2	23.0		-102.4	-102.0
B26	L	23.0+2.7/-4.2	23.4	23.2	-93.8	-102.6	-102.4
	M	23.0±2.7	23.4	23.3		-103.0	-102.8
	H	23.0+2.7/-4.2	23.3	23.3		-102.6	-102.6
B28	L	23.0+2.7/-3.2	23.3	23.1	-94.8	-102.5	-102.5
	M	23.0+2.7/-3.2	23.3	23.2		-103.2	-103.2
	H	23.0+2.7/-3.2	23.2	23.1		-103.0	-102.5
B30	L/M/H	23.0±2.7	23.3	23.2	-95.3	-101.5	-101.5
B66	L	23.0±2.7	22.9	23.1	-95.8	-102.2	-102.0
	M	23.0±2.7	23.0	23.0		-102.0	-101.8

Band	Channel	Maximum TX Power (dBm)			RX Sensitivity (Main+Diversity) (dBm)		
		3GPP Requirement	Test Value		3GPP Requirement	Test Value	
			1460#	8110#		1460#	8110#
B71	H	23.0±2.7	23.0	23.1	-93.5	-102.4	-102.4
	L	23.0+2.7/-3.2	23.4	23.2		-102.1	-102.3
	M	23.0+2.7/-3.2	23.3	23.2		-102.3	-102.5
	H	23.0+2.7/-3.2	23.2	23.1		-102.3	-102.3

Table 7. LTE-FDD maximum TX power & RX sensitivity (main&diversity) (Bandwidth=10M)

Band	Channel	Maximum TX Power (dBm)			RX Sensitivity (dBm)				
		3GPP Requirement	Test Value		3GPP Requirement	Test Value (Main)		Test Value (Diversity)	
			1460#	8110#		1460#	8110#	1460#	8110#
B1	L	23.0±2.7	23.2	23.1	-96.3	-98.7	-98.5	-99.5	-99.5
	M	23.0±2.7	23.2	23.2		-98.9	-98.5	-99.3	-99.3
	H	23.0±2.7	23.1	23.1		-98.5	-98.3	-99.3	-99.1
B2	L	23.0+2.7/-4.2	23.1	23.0	-94.3	-98.7	-98.9	-99.3	-99.1
	M	23.0±2.7	23.2	23.0		-99.3	-99.5	-99.7	-99.7
	H	23.0+2.7/-4.2	23.1	22.9		-99.3	-99.3	-99.5	-99.7
B3	L	23.0+2.7/-4.2	23.0	23.0	-93.3	-98.7	-98.5	-98.9	-99.1
	M	23.0±2.7	23.1	23.1		-98.9	-98.9	-98.7	-99.7
	H	23.0+2.7/-4.2	23.1	23.0		-99.1	-98.9	-99.3	-99.5
B4	L	23.0±2.7	22.9	22.9	-96.3	-98.5	-98.5	-99.5	-99.3
	M	23.0±2.7	23.0	23.0		-99.3	-99.1	-99.3	-99.3
	H	23.0±2.7	22.9	23.0		-98.7	-98.5	-98.9	-99.1
B5	L	23.0±2.7	23.4	23.3	-94.3	-99.1	-99.5	-100.5	-100.3
	M	23.0±2.7	23.4	23.3		-99.1	-99.3	-100.1	-100.1
	H	23.0±2.7	23.3	23.2		-99.1	-99.3	-99.9	-99.9
B7	L	23.0+2.7/-4.2	22.9	22.7	-94.3	-98.1	-98.1	-99.3	-99.3
	M	23.0±2.7	22.8	22.7		-97.9	-97.9	-99.3	-99.3
	H	23.0+2.7/-4.2	23.0	22.9		-98.1	-98.1	-98.9	-99.1
B8	L	23.0+2.7/-4.2	23.4	23.3	-93.3	-99.1	-99.1	-100.1	-100.1
	M	23.0±2.7	23.5	23.3		-99.1	-98.9	-100.3	-100.3

Band	Channel	Maximum TX Power (dBm)			RX Sensitivity (dBm)				
		3GPP Requirement	Test Value		3GPP Requirement	Test Value (Main)		Test Value (Diversity)	
			1460#	8110#		1460#	8110#	1460#	8110#
	H	23.0+2.7/-4.2	23.3	23.3		-99.1	-99.1	-100.1	-100.1
	L	23.0+2.7/-4.2	23.2	23.1		-98.9	-98.7	-98.5	-98.5
B12	M	23.0±2.7	23.2	23.2	-93.3	-98.7	-98.5	-98.9	-98.9
	H	23.0+2.7/-4.2	23.2	23.2		-98.7	-98.5	-99.1	-99.1
B13	L/M/H	23.0±2.7	23.2	23.1	-93.3	-98.7	-98.7	-99.1	-99.1
B14	L/M/H	23.0±2.7	23.2	23.1	-93.3	-98.5	-98.5	-98.7	-98.5
	L	23.0±2.7	23.2	23.1		-98.7	-98.7	-99.1	-99.1
B17	M	23.0±2.7	23.2	23.2	-93.3	-98.9	-98.5	-99.1	-99.1
	H	23.0±2.7	23.2	23.1		-98.7	-98.5	-99.1	-99.1
	L	23.0+2.7/-4.2	23.2	23.2		-99.1	-99.1	-100.1	-100.1
B18	M	23.0±2.7	23.3	23.2	-96.3	-99.1	-99.1	-100.3	-100.3
	H	23.0±2.7	23.4	23.3		-99.1	-99.1	-100.3	-100.3
	L	23.0±2.7	23.4	23.3		-99.3	-99.3	-100.3	-100.3
B19	M	23.0±2.7	23.4	23.3	-96.3	-99.1	-99.3	-100.1	-100.1
	H	23.0±2.7	23.4	23.3		-99.3	-99.3	-99.9	-99.9
	L	23.0+2.7/-4.2	23.3	23.3		-98.7	-98.9	-100.1	-100.1
B20	M	23.0±2.7	23.4	23.3	-93.3	-99.1	-99.1	-99.9	-100.1
	H	23.0+2.7/-4.2	23.4	23.3		-99.1	-99.3	-99.7	-99.7
	L	23.0+2.7/-4.2	23.2	23.0		-98.6	-98.6	-99.4	-99.0
B25	M	23.0±2.7	23.2	23.0	-92.8	-99.2	-99.2	-99.8	-99.6
	H	23.0+2.7/-4.2	23.2	23.0		-99.4	-99.4	-99.6	-99.6
	L	23.0+2.7/-4.2	23.4	23.2		-99.0	-99.0	-100.2	-100.0
B26	M	23.0±2.7	23.4	23.3	-93.8	-99.4	-99.4	-100.4	-100.4
	H	23.0+2.7/-4.2	23.3	23.3		-99.2	-99.4	-100.0	-100.0
	L	23.0+2.7/-3.2	23.3	23.1		-99.2	-99.6	-99.6	-99.6
B28	M	23.0+2.7/-3.2	23.3	23.2	-94.8	-100.0	-100.0	-100.2	-100.2
	H	23.0+2.7/-3.2	23.2	23.1		-99.6	-99.6	-100.0	-100.0
B30	L/M/H	23.0±2.7	23.3	23.2	-95.3	-98.1	-98.1	-98.7	-98.9

Band	Channel	Maximum TX Power (dBm)			RX Sensitivity (dBm)			
		3GPP Requirement	Test Value		3GPP Requirement	Test Value (Main)		Test Value (Diversity)
			1460#	8110#		1460#	8110#	
B66	L	23.0±2.7	22.9	23.1	-95.8	-98.6	-98.7	-99.6
	M	23.0±2.7	23.0	23.0		-98.6	-98.7	-99.2
	H	23.0±2.7	23.0	23.1		-99.2	-99.2	-99.4
B71	L	23.0+2.7/-3.2	23.4	23.2	-93.5	-99.9	-99.9	-98.7
	M	23.0+2.7/-3.2	23.3	23.2		-100.1	-100.1	-98.5
	H	23.0+2.7/-3.2	23.2	23.1		-99.7	-99.7	-98.7

Table 8. Other specifications of LTE-FDD

Band	Test Environment	Protocol Section	Test Case	Result
B1/B2/B3/ B4/B5/B7/ B8/B12/ B13/B14/ B17/B18/ B19/B20/ B25/B26/ B28/B30/ B66/B71	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.2	UE Maximum Output Power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.3	Maximum Power Reduction (MPR)	PASS
	NC	6.2.4	Additional Maximum Power Reduction (A-MPR)	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.5	Configured UE transmitted Output Power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.2	Minimum Output Power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3	Transmit OFF power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.1	General ON/OFF time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.2.1	PRACH time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.2.2	SRS time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.5.1	Power Control Absolute power tolerance	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.5.2	Power Control Relative power tolerance	PASS
	Normal	6.3.5.3	Aggregate power control tolerance	PASS

Band	Test Environment	Protocol Section	Test Case	Result
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.1	Frequency Error	PASS
	NC	6.5.2.1	Error Vector Magnitude (EVM) for PUSCH	PASS
	NC	6.5.2.1	Error Vector Magnitude (EVM) for PUCCH	PASS
	NC	6.5.2.1	Error Vector Magnitude (EVM) for PRACH	PASS
	Normal	6.5.2.1A	PUSCH-EVM with exclusion period	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.2	Carrier leakage	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.3	In-band emissions for non-allocated RB	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.4	EVM equalizer spectrum flatness	PASS
	Normal	6.6.1	Occupied bandwidth	PASS
	NC	6.6.2.1	Spectrum Emission Mask	PASS
	NC	6.6.2.2	Additional Spectrum Emission Mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.6.2.3	Adjacent Channel Leakage Power Ratio	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	7.3	Reference sensitivity level	PASS
	NC	7.4	Maximum input level	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.3_3	Maximum Power Reduction (MPR) for UL 64QAM	PASS
	NC	6.2.4_2	Additional Maximum Power Reduction (A-MPR) for UL 64QAM	PASS
	NC	6.5.2.1_1	Error Vector Magnitude (EVM) for UL 64QAM	PASS
	NC	6.6.2.2_1	Additional Spectrum Emission Mask for UL 64QAM	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.6.2.3_4	Adjacent Channel Leakage Power Ratio for Multi-Cluster PUSCH with UL 64QAM	PASS
	NC	7.4_H	Maximum input level for 256QAM in DL	PASS

5.2 LTE TDD Specifications

Description:

The maximum TX power of LTE TDD is measured by 10M QPSK 1RB. The RB position in low and medium channels is low, and the RB position in high channel is high.

Table 9. LTE-TDD maximum TX power & RX sensitivity (main+diversity) (Bandwidth=10M)

Band	Channel	Maximum TX Power (dBm)				RX Sensitivity (Main+Diversity) (dBm)		
		3GPP Requirement	Test Value			3GPP Requirement	Test Value	
			1460#	8110#			1460#	8110#
B34	L	23.0±2.7	23.0	23.0	-96.3	-101.7	-101.5	
	M	23.0±2.7	23.2	23.1		-101.7	-101.5	
	H	23.0±2.7	23.0	23.1		-101.9	-101.7	
B38	L	23.0±2.7	23.1	22.9	-96.3	-101.9	-101.5	
	M	23.0±2.7	23.2	23.0		-102.1	-101.9	
	H	23.0±2.7	23.1	23.1		-101.7	-101.5	
B39	L	23.0±2.7	23.3	23.1	-96.3	-102.1	-102.1	
	M	23.0±2.7	23.3	23.1		-102.1	-102.1	
	H	23.0±2.7	23.3	23.2		-102.1	-102.1	
B40	L	23.0±2.7	23.4	23.2	-96.3	-101.3	-101.4	
	M	23.0±2.7	23.5	23.2		-101.3	-101.7	
	H	23.0±2.7	23.4	23.2		-100.9	-101.2	
B41	L	23.0+2.7/-4.2	23.1	22.8	-94.3	-100.9	-100.7	
	M	23.0±2.7	23.1	23.0		-101.9	-101.7	
	H	23.0+2.7/-4.2	23.2	23.1		-101.7	-101.5	
B42	L	23.0+3.0/-4.0	23.0	23.3	-95.0	-102.4	-102.2	
	M	23.0+3.0/-4.0	23.2	23.6		-102.2	-102.5	
	H	23.0+3.0/-4.0	23.4	23.5		-102.4	-102.4	
B43	L	23.0+3.0/-4.0	23.4	23.5	-95.0	-102.4	-102.4	
	M	23.0+3.0/-4.0	23.5	23.6		-102.6	-102.4	
	H	23.0+3.0/-4.0	23.4	23.6		-102.6	-102.4	
B48	L	23.0±3.3	23.3	23.6	-95.0	-102.2	-102.4	
	M	23.0±3.3	23.3	23.4		-102.6	-102.4	
	H	23.0±3.3	23.4	23.4		-102.6	-102.4	

Table 10. LTE-TDD maximum TX power & RX sensitivity (main&diversity) (Bandwidth=10M)

Band	Channel	Maximum TX Power (dBm)			RX Sensitivity (dBm)				
		3GPP Requirement	Test Value		3GPP Requirement	Test Value (main)		Test Value (diversity)	
			1460#	8110#		1460#	8110#	1460#	8110#
B34	L	23.0±2.7	23.0	23.0	-96.3	-98.8	-98.5	-98.7	-98.9
	M	23.0±2.7	23.2	23.1		-98.8	-98.5	-98.9	-99.1
	H	23.0±2.7	23.0	23.1		-98.6	-98.5	-99.1	-98.9
B38	L	23.0±2.7	23.1	22.9	-96.3	-99.7	-99.5	-98.1	-98.0
	M	23.0±2.7	23.2	23.0		-99.3	-99.3	-98.3	-98.3
	H	23.0±2.7	23.1	23.1		-99.1	-99.1	-97.7	-97.9
B39	L	23.0±2.7	23.3	23.1	-96.3	-98.5	-98.7	-99.1	-99.3
	M	23.0±2.7	23.3	23.1		-98.5	-98.9	-99.1	-99.1
	H	23.0±2.7	23.3	23.2		-98.5	-98.7	-98.7	-99.1
B40	L	23.0±2.7	23.4	23.2	-96.3	-97.1	-96.9	-98.9	-99.1
	M	23.0±2.7	23.5	23.2		-97.7	-97.5	-98.9	-98.9
	H	23.0±2.7	23.4	23.2		-97.0	-97.0	-98.1	-98.3
B41	L	23.0+2.7/-4.2	23.1	22.8	-94.3	-98.7	-98.9	-97.3	-97.2
	M	23.0±2.7	23.1	23.0		-99.3	-99.3	-98.3	-98.2
	H	23.0+2.7/-4.2	23.2	23.1		-98.9	-98.9	-98.1	-97.7
B42	L	23.0+3.0/-4.0	23.0	23.3	-95.0	-99.4	-99.4	-99.6	-99.4
	M	23.0+3.0/-4.0	23.2	23.6		-99.0	-99.4	-99.2	-99.2
	H	23.0+3.0/-4.0	23.4	23.5		-99.4	-99.6	-99.2	-99.4
B43	L	23.0+3.0/-4.0	23.4	23.5	-95.0	-99.4	-99.6	-99.0	-99.4
	M	23.0+3.0/-4.0	23.5	23.6		-99.8	-99.6	-99.4	-99.4
	H	23.0+3.0/-4.0	23.4	23.6		-99.4	-99.6	-99.2	-99.4
B48	L	23.0±3.3	23.3	23.6	-95.0	-99.2	-99.6	-99.4	-99.6
	M	23.0±3.3	23.3	23.4		-99.4	-99.6	-99.4	-99.6
	H	23.0±3.3	23.4	23.4		-99.6	-99.6	-99.4	-99.4

Table 11. Other specifications of LTE-TDD

Band	Test Environment	Protocol Section	Test Case	Result
B34/B38/	Normal, TL/VL, TL/VH,	6.2.2	UE Maximum Output Power	PASS

Band	Test Environment	Protocol Section	Test Case	Result
B39/B40/ B41/B42/ B43/B48	TH/VL, TH/VH			
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.3	Maximum Power Reduction (MPR)	PASS
	NC	6.2.4	Additional Maximum Power Reduction (A-MPR)	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.5	Configured UE transmitted Output Power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.2	Minimum Output Power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3	Transmit OFF power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.1	General ON/OFF time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.2.1	PRACH time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.2.2	SRS time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.5.1	Power Control Absolute power tolerance	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.5.2	Power Control Relative power tolerance	PASS
	Normal	6.3.5.3	Aggregate power control tolerance	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.1	Frequency Error	PASS
	NC	6.5.2.1	Error Vector Magnitude (EVM) for PUSCH	PASS
	NC	6.5.2.1	Error Vector Magnitude (EVM) for PUCCH	PASS
	NC	6.5.2.1	Error Vector Magnitude (EVM) for PRACH	PASS
	Normal	6.5.2.1A	PUSCH-EVM with exclusion period	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.2	Carrier leakage	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.3	In-band emissions for non-allocated RB	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.4	EVM equalizer spectrum flatness	PASS
	Normal	6.6.1	Occupied bandwidth	PASS

Band	Test Environment	Protocol Section	Test Case	Result
	NC	6.6.2.1	Spectrum Emission Mask	PASS
	NC	6.6.2.2	Additional Spectrum Emission Mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.6.2.3	Adjacent Channel Leakage Power Ratio	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	7.3	Reference sensitivity level	PASS
	NC	7.4	Maximum input level	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.3_3	Maximum Power Reduction (MPR) for UL 64QAM	PASS
	NC	6.2.4_2	Additional Maximum Power Reduction (A-MPR) for UL 64QAM	PASS
	NC	6.5.2.1_1	Error Vector Magnitude (EVM) for UL 64QAM	PASS
	NC	6.6.2.2_1	Additional Spectrum Emission Mask for UL 64QAM	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.6.2.3_4	Adjacent Channel Leakage Power Ratio for Multi-Cluster PUSCH with UL 64QAM	PASS
	NC	7.4_H	Maximum input level for 256QAM in DL	PASS

5.3 LTE HPUE Specifications

Description:

The maximum TX power is measured by 10MHz QPSK 1RB. The RB position in low and medium channels is low, and the RB position in high channel is high.

Table 12. LTE HPUE maximum TX power

Band	Channel	Maximum TX Power (dBm)		
		3GPP Requirement	Test Value	
			1460#	8110#
B38	L	26.0±2.7	25.9	25.8
	M	26.0±2.7	26.1	26.0
	H	26.0±2.7	26.1	26.0
B40	L	26.0±2.7	26.3	26.3
	M	26.0±2.7	26.4	26.2
	H	26.0±2.7	26.3	26.2

Band	Channel	Maximum TX Power (dBm)		
		3GPP Requirement	Test Value	
			1460#	8110#
B41	L	26.0+2.7/-4.2	26.1	25.9
	M	26.0±2.7	26.1	26.0
	H	26.0+2.7/-4.2	26.2	26.1
B42	L	26.0+3/-4	26.0	26.3
	M	26.0+3/-4	26.2	26.7
	H	26.0+3/-4	26.3	26.4
B43	L	26.0+3/-4	26.3	26.6
	M	26.0+3/-4	26.5	26.5
	H	26.0+3/-4	26.3	26.6

Table 13. Other specifications of LTE HPUE

Band	Test Environment	Protocol Section	Test Case	Result
B38/B40/ B41/B42/ B43	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.2_1	UE Maximum Output Power for HPUE	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.3_1	Maximum Power Reduction (MPR) for HPUE	PASS
	NC	6.2.4_1	Additional Maximum Power Reduction (A-MPR) for HPUE	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.5_1	Configured UE transmitted Output Power for HPUE	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.5_1.1	Power Control Absolute power tolerance for HPUE	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.5_1.2	Power Control Relative power tolerance for HPUE	PASS
	Normal	6.3.5_1.3	Aggregate power control tolerance for HPUE	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.6.2.3_1	Adjacent Channel Leakage Power Ratio for HPUE	PASS

5.4 5G RedCap FDD Specifications

Description:

- The maximum TX power of 5G RedCap is measured in FDD SCS=15KHz, TDD SCS=30KHz, UL DFT-s-OFDM QPSK Inner Full RB.

- The RX sensitivity of 5G RedCap is measured in FDD SCS=15KHz, TDD SCS=30KHz, the UL RB configure refer to 3GPP protocol 38.521-1 Table 7.3.2.4.1-3.
- TT is the test tolerance, and the tolerance value of TX power is referred to 3GPP protocol 38.521-1 Table 6.2I.1.5-2, as shown in the following figure.

Table 6.2I.1.5-2: Test Tolerance (UE maximum output power)

	$f \leq 3.0\text{GHz}$	$3.0\text{GHz} < f \leq 4.2\text{GHz}$	$4.2\text{GHz} < f \leq 6.0\text{GHz}$
BW $\leq 40\text{MHz}$	0.7 dB	1.0 dB	1.0 dB

Figure 1. RedCap maximum TX power tolerance

Refer to 3GPP protocol 38.521-1 Table 7.3I.2.5-7 for tolerances of RX sensitivity, as shown in the following figure.

Table 7.3I.2.5-7: Test Tolerance (TT) for RX sensitivity level for RedCap UE

$f \leq 3.0\text{GHz}$	$3.0\text{GHz} < f \leq 6.0\text{GHz}$
0.7 dB	1.0 dB

Figure 2. RedCap Tolerances of RX sensitivity

Table 14. RedCap maximum TX power & RX sensitivity (main+diversity)

Band	BW (MHz)	Channel	Maximum TX Power (dBm)			RX Sensitivity (Main+Diversity) (dBm)		
			3GPP Requirement	Test Value		3GPP requirement	Test Value	
				1007#	9324#		1007#	9324#
n1	20	L	$23 \pm 2 \pm \text{TT}$	22.9	22.7	$-93.8 + \text{TT}$	-99.3	-99.5
		M	$23 \pm 2 \pm \text{TT}$	23.0	22.8		-99.3	-99.5
		H	$23 \pm 2 \pm \text{TT}$	22.9	22.7		-99.1	-99.0
n2	20	L	$23 + 2/-3.5 \pm \text{TT}$	23.1	23.0	$-91.8 + \text{TT}$	-99.7	-100.0
		M	$23 \pm 2 \pm \text{TT}$	23.0	23.0		-99.9	-100.0
		H	$23 + 2/-3.5 \pm \text{TT}$	23.0	22.9		-99.7	-100.0
n3	20	L	$23 + 2/-3.5 \pm \text{T}$	22.8	23.0	$-90.8 + \text{TT}$	-99.3	-99.5
		M	$23 \pm 2 \pm \text{TT}$	22.8	23.1		-99.5	-99.5
		H	$23 + 2/-3.5 \pm \text{TT}$	22.9	23.0		-99.7	-99.5
n5	20	L	$23 \pm 2 \pm \text{TT}$	23.3	23.4	$-86.8 + \text{TT}$	-99.7	-100.0
		M	$23 \pm 2 \pm \text{TT}$	23.2	23.2		-99.7	-100.5
		H	$23 \pm 2 \pm \text{TT}$	23.1	23.1		-99.7	-100.0
		L	$23 + 2/-3.5 \pm \text{TT}$	22.9	23.2		-99.1	-99.5

Band	BW (MHz)	Channel	Maximum TX Power (dBm)			RX Sensitivity (Main+Diversity) (dBm)		
			3GPP Requirement	Test Value		3GPP requirement	Test Value	
				1007#	9324#		1007#	9324#
n7	20	M	23±2±TT	23.0	23.3	-91.8+TT	-98.9	-99.5
		H	23+2/-3.5±TT	23.1	23.3		-98.9	-99.5
n8	20	L	23+2/-3.5±TT	23.3	23.1	-85.8+TT	-99.5	-100.0
		M	23±2±TT	23.2	23.0		-99.5	-100.0
		H	23+2/-3.5±TT	23.3	22.9		-99.3	-100.0
n12	10	L	23+2/-3.5±TT	23.1	23.1	-93.8+TT	-101.5	-102.0
		M	23±2±TT	23.2	23.1		-101.7	-102.0
		H	23+2/-3.5±TT	23.2	23.0		-101.7	-102.5
n13	10	L/M/H	23±2±TT	22.9	23.0	-93.8+TT	-101.9	-102.0
n14	10	L/M/H	23±2±TT	23.0	23.0	-93.8+TT	-101.7	-102.0
n18	10	L	/	23.1	23.2	/	-102.7	-103.5
		M	/	23.0	23.2		-102.9	-103.5
		H	/	23.0	23.3		-102.9	-103.5
n20	20	L	23+2/-3.5±TT	23.1	23.1	-89.8+TT	-99.3	-100.0
		M	23±2±TT	23.1	23.1		-99.3	-100.0
		H	23+2/-3.5±TT	23.1	23.1		-99.1	-100.0
n25	20	L	23+2/-3.5±TT	23.0	22.9	-90.3+TT	-99.6	-100.0
		M	23±2±TT	23.0	22.9		-100.0	-100.0
		H	23+2/-3.5±TT	22.9	22.9		-99.8	-100.0
n26	20	L	23+2/-3.5±TT	23.0	23.3	-87.6+TT	-99.7	-100.0
		M	23±2±TT	23.1	23.3		-99.7	-100.0
		H	23+2/-3.5±TT	23.1	23.2		-99.5	-100.0
n28	20	L	23+2+TT/-2.5-TT	23.3	23.2	-90.8+TT	-99.9	-100.5
		M	23+2+TT/-2.5-TT	23.1	23.2		-99.9	-100.5
		H	23+2+TT/-2.5-TT	23.0	22.9		-99.7	-100.5
n30	10	L/M/H	23±2±TT	22.8	23.3	-95.8+TT	-101.7	-102.0
n66	20	L	23±2±TT	22.9	23.1	-93.3+TT	-99.6	-100.0
		M	23±2±TT	22.7	23.2		-99.6	-99.5

Band	BW (MHz)	Channel	Maximum TX Power (dBm)			RX Sensitivity (Main+Diversity) (dBm)		
			3GPP Requirement	Test Value		3GPP requirement	Test Value	
				1007#	9324#		1007#	9324#
		H	23±2±TT	22.7	23.3		-99.6	-99.5
n70	15	L/M/H	23±2±TT	22.7	23.3	-95.0+TT	-101.1	-101.0
		L	23+2+TT/-2.5-TT	23.0	23.1		-99.5	-100.0
n71	20	M	23+2+TT/-2.5-TT	23.0	22.9	-86.0+TT	-99.5	-100.0
		H	23+2+TT/-2.5-TT	22.9	23.1		-99.5	-100.0

Table 15. RedCap maximum TX power & RX sensitivity (main&diversity)

			Maximum TX Power (dBm)			RX Sensitivity (dBm)				
Band	BW	Channel	3GPP Requirement	Test Value		3GPP Requirement	Test Value (main)		Test Value (diversity)	
				1007#	9324#		1007#	9324#	1007#	9324#
n1	20M	L	23±2±TT	22.9	22.7	-93.8+3+TT	-96.0	-96.5	-96.7	-97.0
		M	23±2±TT	23.0	22.8		-95.9	-96.0	-96.7	-97.0
		H	23±2±TT	22.9	22.7		-95.7	-96.0	-96.5	-96.5
n2	20M	L	23+2/-3.5±TT	23.1	23.0	-91.8+3+TT	-96.5	-97.0	-96.9	-97.0
		M	23±2±TT	23.0	23.0		-96.5	-97.0	-97.1	-97.5
		H	23+2/-3.5±TT	23.0	22.9		-96.5	-97.0	-96.9	-97.0
n3	20M	L	23+2/-3.5±T	22.8	23.0	-90.8+3+TT	-95.9	-96.0	-96.7	-97.0
		M	23±2±TT	22.8	23.1		-96.1	-96.0	-96.9	-97.0
		H	23+2/-3.5±TT	22.9	23.0		-96.3	-96.5	-96.9	-97.0
n5	20M	L	23±2±TT	23.3	23.4	-86.8+3+TT	-95.9	-96.5	-97.3	-98.0
		M	23±2±TT	23.2	23.2		-96.1	-96.5	-97.3	-98.0
		H	23±2±TT	23.1	23.1		-96.1	-96.5	-97.1	-97.5
n7	20M	L	23+2/-3.5±TT	22.9	23.2	-91.8+3+TT	-95.5	-96.0	-96.7	-97.0
		M	23±2±TT	23.0	23.3		-95.3	-95.5	-96.5	-97.0
		H	23+2/-3.5±TT	23.1	23.3		-95.5	-96.0	-96.3	-96.5
n8	20M	L	23+2/-3.5±TT	23.3	23.1	-85.8+3+TT	-95.7	-96.0	-97.1	-97.5
		M	23±2±TT	23.2	23.0		-95.5	-95.5	-97.1	-97.5
		H	23+2/-3.5±TT	23.3	22.9		-95.3	-96.0	-97.1	-97.5

Band	BW	Channel	Maximum TX Power (dBm)		RX Sensitivity (dBm)					
			3GPP Requirement	Test Value		3GPP Requirement	Test Value (main)		Test Value (diversity)	
				1007#	9324#		1007#	9324#	1007#	9324#
n12	10M	L	23+2/-3.5±TT	23.1	23.1	-93.8+3+TT	-98.5	-99.0	-99.0	-99.5
		M	23±2±TT	23.2	23.1		-98.5	-98.5	-99.5	-99.5
		H	23+2/-3.5±TT	23.2	23.0		-98.3	-99.0	-99.5	-100.0
n13	10M	L/M/H	23±2±TT	22.9	23.0	-93.8+3+TT	-98.7	-99.0	-99.5	-100.0
n14	10M	L/M/H	23±2±TT	23.0	23.0	-93.8+3+TT	-98.7	-98.5	-98.7	-99.5
n18	10M	L	/	23.1	23.2	/	-99.5	-100.0	-100.3	-101.0
		M	/	23.0	23.2		-99.5	-100.0	-100.5	-101.0
		H	/	23.0	23.3		-99.5	-99.5	-100.5	-101.0
n20	20M	L	23+2/-3.5±TT	23.1	23.1	-89.8+3+TT	-95.3	-96.0	-96.9	-97.5
		M	23±2±TT	23.1	23.1		-95.7	-96.5	-96.9	-97.5
		H	23+2/-3.5±TT	23.1	23.1		-95.7	-96.5	-96.7	-97.5
n25	20M	L	23+2/-3.5±TT	23.0	22.9	-90.3+3+TT	-96.2	-97.0	-97.0	-97.0
		M	23±2±TT	23.0	22.9		-96.6	-97.0	-97.0	-97.5
		H	23+2/-3.5±TT	22.9	22.9		-96.6	-97.0	-97.0	-97.0
n26	20M	L	23+2/-3.5±TT	23.0	23.3	-87.6+3+TT	-95.9	-96.5	-97.3	-98.0
		M	23±2±TT	23.1	23.3		-95.9	-96.5	-97.3	-98.0
		H	23+2/-3.5±TT	23.1	23.2		-95.9	-96.5	-97.1	-97.5
n28	20M	L	23+2+TT/-2.5-TT	23.3	23.2	-90.8+3+TT	-96.7	-97.0	-96.9	-97.5
		M	23+2+TT/-2.5-TT	23.1	23.2		-96.7	-97.5	-97.1	-98.0
		H	23+2+TT/-2.5-TT	23.0	22.9		-96.5	-97.5	-97.1	-98.0
n30	10M	L/M/H	23±2±TT	22.8	23.3	-95.8+3+TT	-98.3	-98.5	-98.9	-99.5
n66	20M	L	23±2±TT	22.9	23.1	-93.3+3+TT	-96.0	-96.5	-97.0	-97.0
		M	23±2±TT	22.7	23.2		-96.2	-96.5	-96.8	-97.0
		H	23±2±TT	22.7	23.3		-96.2	-96.5	-96.8	-97.0
n70	15M	L/M/H	23±2±TT	22.7	23.3	-95.0+3+TT	-97.9	-98.0	-98.3	-98.5
		L	23+2+TT/-2.5-	23.0	23.1		-97.0	-97.5	-95.7	-96.0

Band	BW	Channel	Maximum TX Power (dBm)			RX Sensitivity (dBm)				
			3GPP Requirement	Test Value		3GPP Requirement	Test Value (main)		Test Value (diversity)	
				1007#	9324#		1007#	9324#	1007#	9324#
n71	20M		TT							
		M	23+2+TT/-2.5-TT	23.0	22.9	-86.0+3+TT	-97.5	-98.0	-95.9	-96.5
		H	23+2+TT/-2.5-TT	22.9	23.1		-97.0	-97.5	-95.5	-96.0

Table 16. Other specifications of RedCap

Band	Test Environment	Protocol Section	Test Case	Result
n1/n2/n3/ n5/n7/n8/ n12/n13/ n14/n18/ n20/n25/ n26/n28/ n30/n66/ n70/n71	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2I.1	UE maximum output power for RedCap	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.2	Maximum Power Reduction (MPR)	PASS
	Normal	6.2.3	UE additional maximum output power reduction	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.4	Configured transmitted power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.1	Minimum output power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.2	Transmit OFF power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3	Transmit ON/OFF time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3.4	PRACH time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3.6	SRS time mask	PASS
	Normal	6.3.4.2	Absolute power tolerance	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.3	Power Control Relative power tolerance	PASS
	Normal	6.3.4.4	Aggregate power tolerance (PUCCH/PUSCH)	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.4.1	Frequency error	PASS

Band	Test Environment	Protocol Section	Test Case	Result
	Normal	6.4.2.1	Error Vector Magnitude (PUCCH/PUSCH/PRACH)	PASS
	Normal	6.4.2.2	Carrier leakage	PASS
	Normal	6.4.2.3	In-band emissions (PUCCH/PUSCH)	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.4.2.4	EVM equalizer spectrum flatness	PASS
	Normal	6.4.2.5	EVM equalizer spectrum flatness for Pi/2 BPSK	PASS
	Normal	6.5.1	Occupied bandwidth	PASS
	Normal	6.5.2.2	Spectrum Emission Mask	PASS
	Normal	6.5.2.3	Additional spectrum emission mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.4	Adjacent channel leakage ratio	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	7.3I.2	Reference sensitivity power level for RedCap	PASS
	Normal	7.4	Maximum input level	PASS

5.5 5G RedCap TDD Specifications

Description:

- The maximum TX power of 5G RedCap is measured in FDD SCS=15KHz, TDD SCS=30KHz, UL DFT-s-OFDM QPSK Inner Full RB.
- The RX sensitivity of 5G RedCap is measured in FDD SCS=15KHz, TDD SCS=30KHz, the UL RB configure refer to 3GPP protocol 38.521-1 Table 7.3.2.4.1-3.
- TT is the test tolerance, and the tolerance value of TX power is referred to 3GPP protocol 38.521-1 Table 6.2I.1.5-2, as shown in the following figure.

Table 6.2I.1.5-2: Test Tolerance (UE maximum output power)

	$f \leq 3.0\text{GHz}$	$3.0\text{GHz} < f \leq 4.2\text{GHz}$	$4.2\text{GHz} < f \leq 6.0\text{GHz}$
BW $\leq 40\text{MHz}$	0.7 dB	1.0 dB	1.0 dB

Figure 3. RedCap maximum TX power tolerance

Refer to 3GPP protocol 38.521-1 Table 7.3I.2.5-7 for tolerances of RX sensitivity, as shown in the following figure.

Table 7.3l.2.5-7: Test Tolerance (TT) for RX sensitivity level for RedCap UE

$f \leq 3.0\text{GHz}$	$3.0\text{GHz} < f \leq 6.0\text{ GHz}$
0.7 dB	1.0 dB

Figure 4. RedCap Tolerances of RX sensitivity

Table 17. RedCap maximum TX power & RX sensitivity (main+diversity)

Band	BW (MHz)	Channel	Maximum TX Power (dBm)			RX Sensitivity (Main+Diversity) (dBm)		
			3GPP Requirement	Test Value		3GPP requirement	Test Value	
				1007#	9324#		1007#	9324#
n38	20	L	23±2±TT	23.0	23.1	-93.8+TT	-99.7	-100.0
		M	23±2±TT	23.0	23.0		-99.7	-100.0
		H	23±2±TT	23.0	23.0		-99.7	-99.5
n40	20	L	23±2±TT	23.1	22.9	-93.8+TT	-99.1	-99.1
		M	23±2±TT	23.2	23.0		-99.3	-99.3
		H	23±2±TT	22.9	23.1		-99.3	-99.1
n41	20	L	23+2/-3.5±TT	22.6	23.1	-91.8+TT	-99.5	-99.5
		M	23±2±TT	22.9	23.0		-99.7	-100.0
		H	23+2/-3.5±TT	22.6	22.9		-99.7	-99.5
n48	20	L	23+2+TT/-3-TT	23.4	23.1	-92.8+TT	-100.7	-101.5
		M	23+2+TT/-3-TT	23.7	23.5		-100.9	-101.5
		H	23+2+TT/-3-TT	23.5	23.2		-100.9	-101.5
n77	20	L	23+2+TT/-3-TT	23.4	23.5	-92.3+TT	-100.0	-100.5
		M	23+2+TT/-3-TT	23.8	23.3		-100.8	-101.5
		H	23+2+TT/-3-TT	24.0	24.0		-100.8	-101.5
n78	20	L	23+2+TT/-3-TT	23.2	23.5	-92.8+TT	-100.1	-100.5
		M	23+2+TT/-3-TT	23.7	23.4		-100.7	-101.5
		H	23+2+TT/-3-TT	23.8	23.8		-100.7	-101.5

Table 18. RedCap maximum TX power & RX sensitivity (main&diversity)

Band	BW	Channel	Maximum TX Power (dBm)		RX Sensitivity (dBm)					
			3GPP Requirement	Test Value		3GPP Requirement	Test Value (main)		Test Value (diversity)	
				1007#	9324#		1007#	9324#	1007#	9324#
n38	20M	L	23±2±TT	23.0	23.1		-97.3	-97.5	-95.9	-96.0
		M	23±2±TT	23.0	23.0	-93.8+2.5+TT	-97.1	-97.5	-96.3	-96.5
		H	23±2±TT	23.0	23.0		-96.9	-97.0	-96.3	-96.0
n40	20M	L	23±2±TT	23.1	22.9		-95.1	-95.1	-96.9	-97.0
		M	23±2±TT	23.2	23.0	-93.8+2.5+TT	-95.7	-95.7	-96.7	-97.0
		H	23±2±TT	22.9	23.1		-95.5	-95.5	-96.5	-96.5
n41	20M	L	23+2/-3.5±TT	22.6	23.1		-97.5	-97.0	-96.0	-96.0
		M	23±2±TT	22.9	23.0	-91.8+2.5+TT	-97.1	-97.5	-96.3	-96.5
		H	23+2/-3.5±TT	22.6	22.9		-97.3	-97.0	-95.9	-96.0
n48	20M	L	23+2+TT/-3-TT	23.4	23.1		-97.7	-98.5	-97.5	-97.5
		M	23+2+TT/-3-TT	23.7	23.5	-92.8+2.5+TT	-97.9	-98.5	-97.5	-98.0
		H	23+2+TT/-3-TT	23.5	23.2		-97.9	-98.5	-97.5	-98.0
n77	20M	L	23+2+TT/-3-TT	23.4	23.5		-97.0	-97.5	-97.2	-96.5
		M	23+2+TT/-3-TT	23.8	23.3	-92.3+2.5+TT	-98.0	-98.5	-97.2	-97.5
		H	23+2+TT/-3-TT	24.0	24.0		-97.8	-98.5	-97.2	-97.5
n78	20M	L	23+2+TT/-3-TT	23.2	23.5		-97.1	-97.5	-96.9	-97.5
		M	23+2+TT/-3-TT	23.7	23.4	-92.8+2.5+TT	-97.7	-98.5	-97.5	-98.0
		H	23+2+TT/-3-TT	23.8	23.8		-97.9	-98.5	-97.5	-97.0

Table 19. Other specifications of RedCap

Band	Test Environment	Protocol Section	Test Case	Result
n38/n40/ n41/n48/ n77/n78	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2I.1	UE maximum output power for RedCap	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.2	Maximum Power Reduction (MPR)	PASS
	Normal	6.2.3	UE additional maximum output power reduction	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.2.4	Configured transmitted power	PASS

Band	Test Environment	Protocol Section	Test Case	Result
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.1	Minimum output power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.2	Transmit OFF power	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3	Transmit ON/OFF time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3.4	PRACH time mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.3.6	SRS time mask	PASS
	Normal	6.3.4.2	Absolute power tolerance	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.3.4.3	Power Control Relative power tolerance	PASS
	Normal	6.3.4.4	Aggregate power tolerance (PUCCH/PUSCH)	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.4.1	Frequency error	PASS
	Normal	6.4.2.1	Error Vector Magnitude (PUCCH/PUSCH/PRACH)	PASS
	Normal	6.4.2.2	Carrier leakage	PASS
	Normal	6.4.2.3	In-band emissions (PUCCH/PUSCH)	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.4.2.4	EVM equalizer spectrum flatness	PASS
	Normal	6.4.2.5	EVM equalizer spectrum flatness for Pi/2 BPSK	PASS
	Normal	6.5.1	Occupied bandwidth	PASS
	Normal	6.5.2.2	Spectrum Emission Mask	PASS
	Normal	6.5.2.3	Additional spectrum emission mask	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	6.5.2.4	Adjacent channel leakage ratio	PASS
	Normal, TL/VL, TL/VH, TH/VL, TH/VH	7.3I.2	Reference sensitivity power level for RedCap	PASS
	Normal	7.4	Maximum input level	PASS

5.6 5G RedCap SRS Specifications

Table 20. SA 1T2R

Band	Channel	Maximum TX Power (dBm)	
		Test Value (TX0)	Test Value (TX0_SRS)
n38	M	21.0	20.4
n40	M	21.2	20.7
n41	M	20.7	20.1
n48	M	20.8	20.5
n77	M	21.1	20.9
n78	M	20.8	20.7

5.7 GNSS Specifications

Table 21. GNSS specifications

Mode	Test Case	Unit	Test Value	
			6742#	6585#
GNSS	Tracking sensitivity	dBm	-157.0	-157.0
	Cold start (RX power@-130dBm)	s	30.5	30.4
	Warm start (RX power@-130dBm)	s	28.5	29.5
	Hot start (RX power@-130dBm)	s	1.5	2.2
	Acquisition Sensitivity at different power level (cold start)	dBm	-146.0	-146.0
	Position Accuracy (cold start@-130dBm, CEP 50%)	m	1.0	0.6
	C/N0 (RX power@-130dBm)	dB/Hz	38.8	38.8
	Current consumption fixing (Cold start - average current until TTFF with 20SVs @-130dBm)	mA	44.0	44.2
	Current consumption tracking (Weak signal, 20SVs @-146dBm, no power saving, fix rate=1sec)	mA	45.8	44.9

5.8 Max Throughput

Single Band Max throughput

Description:

- For LTE single band maximum physical layer throughput test, the BW is the maximum BW defined by

the 3GPP protocol. The uplink-downlink configurations of the TDD band to be set 5 when DL max physical layer throughput test, and to be set 0 when UL max physical layer throughput test, and the special subframe is 4.

- For SA single band maximum physical layer throughput test, the BW is the maximum BW defined by the 3GPP protocol. The FDD SCS is 15kHz, TDD SCS is 30kHz, the uplink-downlink configurations of the TDD band to be set 5ms 8DS1U S(10:2:2) when DL max physical layer throughput test, and to be set 3DS6U S(10:2:2) when UL max physical layer throughput test.

Table 22. Single Band Max throughput

System	Band	BW	Channel	DL Theoretical Value (Mbps)	DL Test Value (Mbps)	UL Theoretical Value (Mbps)	UL Test Value (Mbps)
LTE-FDD RMS	B1	20M	CH18100	194.973	194.973	75.376	75.376
			CH18300	194.973	194.973	75.376	75.376
			CH18500	194.973	194.973	75.376	75.376
	B2	20M	CH18700	194.973	194.973	75.376	75.376
			CH18900	194.973	194.973	75.376	75.376
			CH19100	194.973	194.973	75.376	75.376
	B3	20M	CH19300	194.973	194.973	75.376	75.376
			CH19575	194.973	194.973	75.376	75.376
			CH19850	194.973	194.973	75.376	75.376
	B4	20M	CH20050	194.973	194.973	75.376	75.376
			CH20175	194.973	194.973	75.376	75.376
			CH20300	194.973	194.973	75.376	75.376
	B5	10M	CH20450	97.462	97.462	36.696	36.696
			CH20525	97.462	97.462	36.696	36.696
			CH20600	97.462	97.462	36.696	36.696
	B7	20M	CH20850	194.973	194.973	75.376	75.376
			CH21100	194.973	194.973	75.376	75.376
			CH21350	194.973	194.973	75.376	75.376
	B8	10M	CH21500	97.462	97.462	36.696	36.696
			CH21625	97.462	97.462	36.696	36.696
			CH21750	97.462	97.462	36.696	36.696
	B12	10M	CH23060	97.462	97.462	36.696	36.696
			CH23095	97.462	96.973	36.696	36.696

System	Band	BW	Channel	DL Theoretical Value (Mbps)	DL Test Value (Mbps)	UL Theoretical Value (Mbps)	UL Test Value (Mbps)
LTE-TDD RMS	B13	10M	CH23130	97.462	97.462	36.696	36.696
			CH23230	97.462	97.462	36.696	36.696
			CH23330	97.462	97.462	36.696	36.696
	B17	10M	CH23780	97.462	97.462	36.696	36.696
			CH23790	97.462	97.462	36.696	36.696
			CH23800	97.462	97.462	36.696	36.696
	B18	15M	CH23925	149.899	149.899	55.056	55.056
	B19	15M	CH24075	149.899	149.899	55.056	55.056
	B20	20M	CH24250	194.973	194.973	75.376	75.376
			CH24300	194.973	194.973	75.376	75.376
			CH24350	194.973	194.973	75.376	75.376
	B25	20M	CH26115	194.973	194.973	75.376	75.376
			CH26365	194.973	194.973	75.376	75.376
			CH26615	194.973	194.973	75.376	75.376
	B26	15M	CH26765	149.899	149.899	55.056	55.056
			CH26865	149.899	149.899	55.056	55.056
			CH26965	149.899	149.899	55.056	55.056
	B28	20M	CH27310	194.973	194.973	75.376	75.376
			CH27460	194.973	194.973	75.376	75.376
			CH27560	194.973	194.973	75.376	75.376
	B30	10M	CH27710	97.462	97.462	36.696	36.696
	B66	20M	CH132072	194.973	194.973	75.376	75.376
			CH132422	194.973	194.973	75.376	75.376
			CH132572	194.973	194.973	75.376	75.376
	B71	20M	CH133222	194.973	194.973	75.376	75.376
			CH133322	194.973	194.973	75.376	75.376
			CH133372	194.973	194.973	75.376	75.376
LTE-TDD RMS	B34	15M	CH36275	130.76	130.76	33.034	33.034
			CH37850	170.89	170.89	45.226	45.226

System	Band	BW	Channel	DL Theoretical Value (Mbps)	DL Test Value (Mbps)	UL Theoretical Value (Mbps)	UL Test Value (Mbps)
	B38	20M	CH38000	170.89	170.89	45.226	45.226
			CH38150	170.89	170.89	45.226	45.226
	B39	20M	CH38350	170.89	170.89	45.226	45.226
			CH38450	170.89	170.89	45.226	45.226
			CH38550	170.89	170.89	45.226	45.226
	B40	20M	CH38750	170.89	170.89	45.226	45.226
			CH39150	170.89	170.89	45.226	45.226
			CH39550	170.89	170.89	45.226	45.226
	B41	20M	CH39750	170.89	170.89	45.226	45.226
			CH40620	170.89	170.89	45.226	45.226
			CH41490	170.89	170.89	45.226	45.226
	B42	20M	CH41690	170.89	170.89	45.226	45.226
			CH42590	170.89	170.89	45.226	45.226
			CH43490	170.89	170.89	45.226	45.226
	B43	20M	CH43690	170.89	170.89	45.226	45.226
			CH44590	170.89	170.89	45.226	45.226
			CH45490	170.89	170.89	45.226	45.226
	B48	20M	CH55340	170.89	170.89	45.226	45.226
			CH55990	170.89	170.89	45.226	45.226
			CH56640	170.89	170.89	45.226	45.226
RedCap FDD RMS	n1	20M	CH424000	230.74	230.74	122.98	122.98
			CH428000	231.15	231.15	122.98	122.98
			CH432000	230.95	230.95	122.98	122.98
	n2	20M	CH388000	230.74	230.74	122.98	122.98
			CH392000	231.15	231.15	122.98	122.98
			CH396000	230.95	230.95	122.98	122.98
	n3	20M	CH363000	231.36	231.36	122.98	122.98
			CH368500	231.36	231.36	122.98	122.98
			CH374000	231.15	231.15	122.98	122.98

System	Band	BW	Channel	DL Theoretical Value (Mbps)	DL Test Value (Mbps)	UL Theoretical Value (Mbps)	UL Test Value (Mbps)
	n5	20M	CH175800	231.36	231.36	122.98	122.98
			CH176300	231.36	231.36	122.98	122.98
			CH176800	230.74	230.74	122.98	122.98
	n7	20M	CH526000	230.74	230.74	122.98	122.98
			CH531000	231.36	231.36	122.98	122.98
			CH536000	231.15	231.15	122.98	122.98
	n8	20M	CH187000	231.15	231.15	122.98	122.98
			CH188500	231.36	231.36	122.98	122.98
			CH190000	230.74	230.74	122.98	122.98
	n12	15M	CH147300	173.24	173.24	92.2	92.2
			CH147500	173.85	173.85	92.2	92.2
			CH147700	173.85	173.85	92.2	92.2
	n13	10M	CH150200	111.91	111.91	60.46	60.46
	n14	10M	CH152600	111.91	111.91	60.46	60.46
	n18	15M	CH173500	173.55	173.55	92.2	92.2
	n20	20M	CH160200	231.36	231.36	122.98	122.98
			CH161200	230.74	230.74	122.98	122.98
			CH162200	230.74	230.74	122.98	122.98
	n25	20M	CH388000	230.74	230.74	122.98	122.98
			CH392500	231.36	231.36	122.98	122.98
			CH397000	231.15	231.15	122.98	122.98
	n26	20M	CH173800	231.15	231.15	122.98	122.98
			CH175300	231.36	231.36	122.98	122.98
			CH176800	230.74	230.74	122.98	122.98
	n28	20M	CH153600	230.95	230.95	122.98	122.98
			CH156600	231.36	231.36	122.98	122.98
			CH158600	230.74	230.74	122.98	122.98
	n30	10M	CH471000	112.52	112.52	60.46	60.46
			CH424000	230.74	230.74	122.98	122.98

System	Band	BW	Channel	DL Theoretical Value (Mbps)	DL Test Value (Mbps)	UL Theoretical Value (Mbps)	UL Test Value (Mbps)
RedCap TDD RMS	n66	20M	CH429000	231.36	231.36	122.98	122.98
			CH434000	231.15	231.15	122.98	122.98
	n70	15M	CH400500	173.24	173.24	92.2	92.2
	n71	20M	CH125400	231.36	231.36	122.98	122.98
			CH126900	230.74	230.74	122.98	122.98
			CH128400	230.95	230.95	122.98	122.98
	n38	20M	CH516000	193.31	193.31	78.08	78.08
			CH519000	193.31	193.31	78.08	78.08
			CH522000	193.31	193.31	78.08	78.08
RedCap TDD RMS	n40	20M	CH462000	193.31	193.31	78.08	78.08
			CH470000	193.21	193.21	78.08	78.08
			CH478000	193.56	193.56	78.08	78.08
	n41	20M	CH501204	193.31	193.31	78.08	78.08
			CH518598	193.21	193.21	78.08	78.08
			CH535998	193.41	193.41	78.08	78.08
	n48	20M	CH637334	193.21	193.21	78.08	78.08
			CH641666	193.21	193.21	78.08	78.08
			CH646000	193.31	193.31	78.08	78.08
	n77	20M	CH620668	193.31	193.31	78.08	78.08
			CH650000	193.56	193.56	78.08	78.08
			CH679332	193.41	193.41	78.08	78.08
	n78	20M	CH620668	193.31	193.31	78.08	78.08
			CH636666	193.21	193.21	78.08	78.08
			CH652666	193.41	193.41	78.08	78.08

5.9 Working Current

1. Test conditions: normal temperature of 25°C/3.8V
2. Test data:

Table 23. Single band working current

System	Band	Channel	1460#		8110#	
			Test value (mA)	Power (dBm)	Test value (mA)	Power (dBm)
LTE-FDD RMS (10MHz 1RB)	B1	CH18050	606	23.2	609	23.1
		CH18300	572	23.2	550	23.2
		CH18550	616	23.1	586	23.1
	B2	CH18650	562	23.1	554	23.0
		CH18900	597	23.2	598	23.0
		CH19150	580	23.1	535	22.9
	B3	CH19250	599	23.0	567	23.0
		CH19575	634	23.1	602	23.1
		CH19900	665	23.1	662	23.0
	B4	CH20000	584	22.9	562	22.9
		CH20175	611	23.0	599	23.0
		CH20350	577	22.9	555	23.0
	B5	CH20450	625	23.4	609	23.3
		CH20525	585	23.4	566	23.3
		CH20600	623	23.3	609	23.2
	B7	CH20800	685	22.9	683	22.7
		CH21100	632	22.8	628	22.7
		CH21400	753	23.0	734	22.9
	B8	CH21500	547	23.4	548	23.3
		CH21625	548	23.5	533	23.3
		CH21750	580	23.3	571	23.3
	B12	CH23060	544	23.2	535	23.1
		CH23095	568	23.2	539	23.2
		CH23130	646	23.2	616	23.2
	B13	CH23230	601	23.2	602	23.1
	B14	CH23330	528	23.2	525	23.1
	B17	CH23780	588	23.2	564	23.1
		CH23790	617	23.2	590	23.2

System	Band	Channel	1460#		8110#	
			Test value (mA)	Power (dBm)	Test value (mA)	Power (dBm)
	B18	CH23800	648	23.2	616	23.1
		CH23900	578	23.2	566	23.2
		CH23925	560	23.3	551	23.2
		CH23950	554	23.4	541	23.3
	B19	CH24050	556	23.4	540	23.3
		CH24075	560	23.4	549	23.3
		CH24100	565	23.4	550	23.3
	B20	CH24200	627	23.3	627	23.3
		CH24300	570	23.4	557	23.3
		CH24400	588	23.4	579	23.3
	B25	CH26090	561	23.2	550	23.0
		CH26365	590	23.2	592	23.0
		CH26640	628	23.2	591	23.0
	B26	CH26740	640	23.4	620	23.2
		CH26865	607	23.4	590	23.3
		CH26990	609	23.3	595	23.3
	B28	CH27260	559	23.3	531	23.1
		CH27410	546	23.3	529	23.2
		CH27610	553	23.2	536	23.1
	B30	CH27710	711	23.3	689	23.2
	B66	CH132022	584	22.9	567	23.1
		CH132422	563	23.0	541	23.0
		CH132622	605	23.0	577	23.1
	B71	CH133172	614	23.4	576	23.2
		CH133297	490	23.3	481	23.2
		CH133422	547	23.2	520	23.1
LTE-TDD RMS (10MHz 1RB)	B34	CH36250	313	23.0	308	23.0
		CH36275	314	23.2	309	23.1
		CH36300	312	23.0	306	23.1

System	Band	Channel	1460#		8110#	
			Test value (mA)	Power (dBm)	Test value (mA)	Power (dBm)
	B38	CH37800	404	23.1	411	22.9
		CH38000	391	23.2	385	23.0
		CH38200	343	23.1	339	23.1
	B39	CH38300	271	23.3	280	23.1
		CH38450	271	23.3	283	23.1
		CH38600	276	23.3	288	23.2
	B40	CH38700	424	22.8	399	22.9
		CH39150	364	22.6	348	22.6
		CH39600	385	22.8	358	22.7
	B41	CH39700	366	23.1	351	22.8
		CH40620	364	23.1	372	23.0
		CH41540	357	23.2	347	23.1
	B42	CH41640	331	23.0	310	23.3
		CH42590	359	23.2	321	23.6
		CH43540	323	23.4	312	23.5
	B43	CH43640	310	23.4	304	23.5
		CH44590	315	23.5	291	23.6
		CH45540	309	23.4	295	23.6
	B48	CH55290	331	23.3	312	23.6
		CH55990	305	23.3	300	23.4
		CH56690	313	23.4	291	23.4
LTE-TDD RMS (10MHz 1RB)	B38	CH37800	545	25.9	559	25.8
		CH38000	544	26.1	564	26.0
		CH38200	506	26.1	507	26.0
	B40	CH38700	597	25.8	588	25.8
		CH39150	515	25.6	502	25.7
		CH39600	599	25.7	575	25.9
	B41	CH39700	545	26.1	524	25.9
		CH40620	545	26.1	566	26.0

System	Band	Channel	1460#		8110#	
			Test value (mA)	Power (dBm)	Test value (mA)	Power (dBm)
RedCap RMS (10MHz Inner_Ful)	B42	CH41540	531	26.2	517	26.1
		CH41640	443	26.0	421	26.3
		CH42590	490	26.2	439	26.7
		CH43540	430	26.3	421	26.4
		CH43640	410	26.3	404	26.6
		CH44590	415	26.5	384	26.5
		CH45540	409	26.3	393	26.6
	B43	CH423000	567	22.9	579	22.7
		CH428000	545	23.0	543	22.8
		CH433000	575	22.9	593	22.7
	n1	CH387000	530	23.1	540	23.0
		CH392000	572	23.0	588	23.0
		CH397000	538	23.0	547	22.9
	n2	CH362000	569	22.8	550	23.0
		CH368500	627	22.8	610	23.1
		CH375000	704	22.9	707	23.0
	n3	CH174800	578	23.3	565	23.4
		CH176300	569	23.2	563	23.2
		CH177800	566	23.1	554	23.1
	n5	CH525000	710	22.9	709	23.2
		CH531000	674	23.0	675	23.3
		CH537000	777	23.1	776	23.3
	n7	CH186000	532	23.3	537	23.1
		CH188500	532	23.2	529	23.0
		CH191000	546	23.3	549	22.9
	n8	CH146800	566	23.1	533	23.1
		CH147500	597	23.2	554	23.1
		CH148200	557	23.2	520	23.0
	n12	CH150200	555	22.9	549	23.0
	n13	CH150200	555	22.9	549	23.0

System	Band	Channel	1460#		8110#	
			Test value (mA)	Power (dBm)	Test value (mA)	Power (dBm)
	n14	CH152600	531	23.0	515	23.0
	n18	CH173000	578	23.1	567	23.2
		CH173500	584	23.0	577	23.2
		CH174000	590	23.0	583	23.3
	n20	CH159200	614	23.1	606	23.1
		CH161200	589	23.1	574	23.1
		CH163200	607	23.1	618	23.1
	n25	CH387000	506	23.0	520	22.9
		CH392500	593	23.0	563	22.9
		CH398000	559	22.9	520	22.9
	n26	CH172800	595	23.0	584	23.3
		CH175300	578	23.1	562	23.3
		CH177800	578	23.1	566	23.2
	n28	CH152600	582	23.3	546	23.2
		CH156100	568	23.1	550	23.2
		CH159600	558	23.0	533	22.9
	n30	CH471000	755	22.8	742	23.3
		CH423000	562	22.9	569	23.2
	n66	CH429000	513	22.8	529	23.3
		CH435000	513	22.9	535	23.1
	n70	CH400000	614	22.7	622	23.2
		CH400500	612	22.7	610	23.3
		CH401000	609	22.7	603	23.3
	n71	CH124400	587	23.0	538	23.1
		CH126900	537	23.0	482	22.9
		CH129400	526	22.9	515	23.1
RedCap RMS	TDD n38	CH516000	217	23.0	228	23.1
		CH519000	213	23.0	222	23.0
		CH522000	201	23.0	217	23.0

System	Band	Channel	1460#		8110#	
			Test value (mA)	Power (dBm)	Test value (mA)	Power (dBm)
(20MHz Inner_Ful)	n40	CH462000	224	22.6	217	22.7
		CH470000	210	22.8	204	22.9
		CH478000	191	22.8	185	23.0
	n41	CH501204	179	22.6	197	23.1
		CH518598	219	22.9	221	23.0
		CH535998	211	22.6	225	22.9
	n48	CH637334	197	23.4	202	23.1
		CH641666	190	23.7	204	23.5
		CH646000	187	23.5	198	23.2
	n77	CH620668	210	23.4	217	23.5
		CH650000	199	23.8	202	23.3
		CH679332	294	24.0	284	24.0
	n78	CH620668	208	23.2	217	23.5
		CH636666	216	23.7	217	23.4
		CH652666	199	23.8	207	23.8